

Hydraulic Series Scissor Lifts

0408S/M(1530S/1532M)

0608S/M(1930S/1932M)

Compliance with ISO/CE/ANSI/CSA/AS/CU-TR/KCS standards

Product Highlights

Efficient and environmentally friendly

- Small turning radius, flexible operation in narrow spaces
- Standard forklift slot, for efficient equipment transportation
- Folding guardrails for easy transport

Reduced maintenance costs

- Double-door design for easy maintenance
- Troubleshooting for quick fault diagnosis
- Highly quality parts and components

More reliable performance

- Battery voltage early warning to ensure battery life
- Bumper rail protection
- The pothole protection reporting and horizontal protection system give peace of mind during operation

Standard features		
■ Maintenance-free battery	■ Automatic braking system	■ Drive at full height
■ Proportional control	■ Emergency lowering system	■ Forklift pocket and lifting eyes
■ Bumper rail	■ Emergency stop at both platform and ground controls	■ Electrophoresic painting technology
■ 4x2 drive	■ Fault diagnosis system	■ Foldable guardrail
■ Non-marking tyres	■ Tilt protection	■ Overload sensing system
■ Integrated hand shield	■ Automatic pothole guard	
Optional features		
■ Overhead anti-collision device	■ Headlight	■ RCBO
■ AC power to platform		

SINOBOOM

Sinoboom Intelligent Equipment Co Ltd

📍 No.128 East Jinzhou Av., Ningxiang Hi-Tech Industry Park,
Changsha, Hunan, China, 410600

🌐 www.sinoboom.com

✉ sales@sinoboom.com

Hydraulic Series Scissor Lifts

0408S/M(1530S/1532M)

0608S/M(1930S/1932M)

Compliance with ISO/CE/ANSI/CSA/AS/CU-TR/KCS standards

SINOBOOM

Model		0408S/M(1530S/1532M)		0608S/M(1930S/1932M)	
Dimensions		Metric	US	Metric	US
Max Working Height		6.6m	21'8"	7.8m	25'7"
A	Max Platform Height	4.6m	15'1"	5.8m	19'
B	Max Horizontal Extension	0.9m	3'	0.9m	3'
C	Length-Stowed	1.78m	5'10"	1.78m	5'10"
D	Width-Stowed	0.76m/0.81m	2'6"/2'8"	0.76m/0.81m	2'6"/2'8"
Height	Stowed(Rail Folded)	1.84m	6'	1.86m	6'1"
	E Stowed (Rail Unfolded)	2.1m	6'11"	2.12m	6'11.5"
	Stowed(Fixed Rail)	2.1m	6'11"	2.12m	6'11.5"
	Stowed(Fixed Rail)	1.98m	6'6"	2m	6'7"
F	Wheelbase	1.325m	4'4"	1.325m	4'4"
Ground Clearance		70mm	2.8"	70mm	2.8"
Platform Dimensions(L×W×H)		1.64m×0.76m×1.1m(5'5"×2'6"×3'7")		1.64m×0.76m×1.1m(5'5"×2'6"×3'7")	
Performance					
Platform Allowable Occupants (Indoor/Outdoor)		0408S(1530S): 2 persons/- 0408M(1532M): 2 persons/1 person		0608S(1930S): 2 persons/- 0608M(1932M): 2 persons/1 person	
Platform Capacity		280kg	617lbs	230kg	507lbs
Drive Speed-Stowed		3km/h	1.86mph	3km/h	1.86mph
Drive Speed-Raised		0.8km/h	0.5mph	0.8km/h	0.5mph
Elevation Time(Unloaded)		15s~20s		15s~20s	
Descent Time(Unloaded)		28s~33s		25s~30s	
Gradeability		30%		25%	
Turning Radius(Inside/Outside)		0/1.49m	0/4'11"	0/1.49m	0/4'11"
Tilt Rating(Front to Back/Side to Side)		3°/1.5°		3°/1.5°	
Tyres-solid		305×115mm	12"×4.5"	305×115mm	12"×4.5"
Power					
Batteries		6V×4/225Ah		6V×4/225Ah	
Power Source		24V DC		24V DC	
Drive Mode		2WD, front wheel		2WD, front wheel	
Charger Input		100~240V AC		100~240V AC	
Charger Output		25A		25A	
Brake		2 rear wheel		2 rear wheel	
Hydraulic System Capacity		14L	3gal	14L	3gal
Weight					
Weight		1,330kg	2,932lbs	1,526kg	3,365lbs
		0408S(1530S) for indoor only		0608S(1930S) for indoor only	
Standards Compliance		ISO/CE/ANSI/CSA/AS/CU-TR/KCS			

